

Premium Water-Based 2 part High Performance Urethane Top Coat

Product Features:

- Finish Options:High Gloss or Matte finish!
- UV resistant, non-yellowing
- Excellent chemical resistance; recommended as anti-graffiti topcoat
- Great scratch & abrasion resistance
- Easy to use 50 VOC low odor formula
- Excellent hot tire pick-up resistance
- Recommended for vertical or horizontal applications





Poly-3 WB is a premium clear water-based two-part high performance urethane coating which utilizes aliphatic urethane polymer technology. It provides excellent film hardness, chemical, abrasion and UV resistance and with less than 50 grams/liter VOC, it is approved for use in South Coast Air Quality Management District (SCAQMD). Dura-Shell can be applied directly to many surfaces without the need of a primer, i.e., concrete, wood, aluminum and galvanized metal. The coating is widely used to provide a high gloss or matte finish to concrete floors, food & beverage and pharmaceutical facilities. It is recommended on floors and walls in equipment and clean rooms, as well as amusement parks, refineries, power industry, storage tank exteriors and wastewater facilities.

PERFECT FOR:

- Food processing areas
- Amusement parks
- Bottling areas
- Clean rooms
- · Sanitize/wash areas
- Kitchens
- · Cook/chill areas

- Pharmaceutical plants
- Refineries, chemical processing facilities
- Prison floors
- Storage tank/pipeline exteriors
- · Warehouse floors

Steps	Coverage				
	Rolle Vertical	er Size Horizontal	Sq. Ft./ Gal	M Wet	ils Dry
Clear Coat 1	1" woven nap	3/8" woven nap	250-400	4.0	2.4
Clear Coat 2	1" woven nap	3/8" woven nap	250-400	4.0	2.4

Coverage rates are approximate and for estimating purposes only. Surface temperature, porosity, texture and thickness will determine actual material requirements.







Contact us for more information, (866) 765-4310