
POLYUREA-350 PRIMER/BASECOAT

CFFS Polyurea-350™ is a two-component, 98% solids Polyurea primer/basecoat with unique physical characteristics that make it a one-of-a-kind product. Due to its proprietary blend of resins, Polyurea-350 allows installers to “wet-out” large areas, including vertical surfaces before broadcasting decorative aggregates such as quartz, vinyl chips, or flint. This longer “open time” results in perfect broadcasts every time, eliminating problems with light coverage, inconsistencies, or blemishes. CFFS Adjustable Cure Rate Technology™ allows the installer to customize the workability and cure times of this material for use in any climate. Standard cure times of this revolutionary product can range from 1 hour to 3 hours based on the speed of material used and the temperature at the time of application. This advancement once again shows Citadel Floor Finishing Systems’ commitment to being the market leader in easy to apply floor coating systems. Installations completed with CFFS Polyurea-350 will save hours of time over conventional systems and will cut consumable costs in half. It is hands-down the BEST floor coating product on the market today, backed by a strong warranty, countless months of testing, and thousands of square feet of proven success. Polyurea-350 is available in two formats – Standard, sold clear to allow the installer to customize the color of the floor being installed using CFFS tints; and Traffic Coat, a pre-tinted version that eases in the installation process by eliminating adding of the tint. Both styles dry quickly with exceptional adhesion to a number of substrates and the high solids content makes it a great choice for both interior and exterior applications requiring minimal to no odor.

