

ADDITIVE	TECHNICAL DATA	CDL-19
	CITADEL[®] ULTRA DURABILITY PLUS ADDITIVE	

DESCRIPTION AND USES

Citadel[®] Ultra Durability Plus Additive forms a co-polymer matrix that provides a tough, durable finish with increased protection from marring, scratching and abrasion. This lightweight additive is easy to mix into our coatings and stays in suspension longer than typical stir-in products. When used with our thin mil systems like Poly-1 HD or Poly-3 WB, it provides a satin-texture that helps hide minor imperfections in the substrate and finish on your floors.

PRODUCT FEATURES

- Lightweight, easy to mix and install
- Uniform satin-texture helps hide minor imperfections: wear patterns, roller lint, etc. in thin mil installations
- Will not distort or discolor decorative effects or graphics

PRODUCT

SKU	DESCRIPTION (1/2 pound bag)
15303	Ultra Durability Plus Additive

RECOMMENDED COATINGS

Any floor coating with a dry film thickness of 4 mils or less

PRIMARY APPLICATIONS

- Industrial facilities
- Retail environments
- Showroom environments
- Aircraft hangar floors
- Manufacturing facilities
- Maintenance facilities
- Industrial shop floors
- Warehouse floors
- Grocery stores

PRODUCT APPLICATION

The Ultra Durability Plus Additive can be mixed directly into the coating. Use 1/2 pound of additive per gallon of coating. Stir the container frequently to ensure the additive does not settle out. Apply the coating by roller.

PHYSICAL PROPERTIES

		ULTRA DURABILITY PLUS ADDITIVE
Composition		Thermoset Polymer Resin
Weight	Per Gallon	10.9 lbs
	Per Liter	1.3 kg/l
Solids	By Weight	100%
	By Volume	100%
Volatile Organic Compounds		0
Shelf Life		5 years
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.